

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

THE CLAIMS

1. (Currently Amended) An aerial vehicle recovery system comprising:

a landing pad configured to be supported on a supporting surface, the landing pad comprising an upwardly facing capture surface comprising a passive retaining medium; and

a shoe configured to be mounted to a landing element of an aerial vehicle, the shoe comprising a passive retaining medium fixed thereto and configured to interface with the passive retaining medium of the landing pad to retain the aerial vehicle directly to the landing pad with no further forward motion component of the vehicle with respect to the landing pad upon affixation.

2. (Original) The system of claim 1, wherein the landing pad further comprises a base, and the passive retaining medium of the landing pad comprises a passive engagement component supported by the base.

3. (Original) The system of claim 2, wherein the passive engagement system component of the landing pad extends from a substrate supported by the base.

4. (Original) The system of claim 3, wherein the passive engagement system component of the landing pad comprises a plurality of stems extending from the substrate.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

5. (Original) The system of claim 3, wherein the substrate is affixed to an upper surface of the base of the landing pad.
6. (Original) The system of claim 3, wherein the substrate is integrally formed with the base of the landing pad.
7. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a passive engagement component.
8. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a sticky medium.
9. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a tape.
10. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises an adhesive.
11. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a putty.
12. (Original) The system of claim 1, wherein the shoe further comprises a base and the passive retaining medium of the shoe comprises a passive engagement component supported by the base.
13. (Original) The system of claim 12, wherein the passive engagement system component of the shoe extends from a substrate supported by the base.

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

14. (Original) The system of claim 13, wherein the passive engagement system component of the shoe comprises a plurality of stems extending from the substrate.
15. (Original) The system of claim 13, wherein the substrate is affixed to a lower surface of the base of the shoe.
16. (Original) The system of claim 13, wherein the substrate is integrally formed with the base of the shoe.
17. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a passive engagement component.
18. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a sticky medium.
19. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a tape.
20. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises an adhesive.
21. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a putty.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

22. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise self-engaging fasteners.
23. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise hook and loop fasteners.
24. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise hook-to-hook fasteners.
25. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise stems each having a stalk terminating with a hook.
26. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise stems each having a stalk terminating with a cap.
27. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise an elastomeric material.
28. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise a polyolefin material.

-5-

WEINGARTEN, SCHUBERT,  
GAGNEPAIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

29. (Original) The system of claim 1, wherein the landing pad further comprises a base including load carrying members operative to transfer a load on the landing pad to a supporting surface.

30. (Original) The system of claim 29, wherein the base of the landing pad comprises a composite material comprising the load carrying members embedded in a matrix material.

31. (Original) The system of claim 30, wherein the matrix material comprises a polyurethane material.

32. (Original) The system of claim 29, wherein the load carrying members are oriented unidirectionally.

33. (Original) The system of claim 29, wherein the load carrying members comprise a fiberglass material.

34. (Original) The system of claim 29, wherein the load carrying members comprise rods.

35. (Original) The system of claim 29, wherein the load carrying members comprise flexible straps.

36. (Original) The system of claim 1, wherein the landing pad is rollable.

37. (Withdrawn) The system of claim 1, wherein the landing pad is foldable.

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

38. (Original) The system of claim 1, wherein the landing pad is flexible.

39. (Original) The system of claim 1, wherein the landing pad is resilient.

40. (Original) The system of claim 1, wherein the landing pad is energy-absorbing.

41. (Original) The system of claim 1, wherein the landing pad further comprises a plurality of pad sections and one or more joint fittings configured to attach the plurality of pad sections together.

42. (Original) The system of claim 41, further comprising load carrying members extending transversely across joints between the pad sections.

43. (Original) The system of claim 41, wherein the joint fittings comprise hinged joint fittings.

44. (Original) The system of claim 41, wherein the joint fittings are removably affixed to the pad sections.

45. (Original) The system of claim 1, wherein the landing pad further comprises a plurality of pad sections and a joint attachment mechanism configured to attach the plurality of pad sections together.

-7-

WEINGARTEN, SCHURGIN,  
CRANEIN & LESOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

46. (Withdrawn) The system of claim 1, wherein the landing pad further comprises a plurality of pad sections attached together along hinged joints.

47. (Withdrawn) The system of claim 46, wherein the hinged joints are integral with the pad sections.

48. (Withdrawn) The system of claim 46, wherein the hinged joints are permanently affixed to the pad sections.

49. (Withdrawn) The system of claim 46, wherein the hinged joints are removably affixed to the pad sections.

50. (Withdrawn) The system of claim 1, wherein the landing pad further includes an energy-absorbing layer.

51. (Withdrawn) The system of claim 1, wherein the landing pad further includes an energy-absorbing layer between two panels.

52. (Withdrawn) The system of claim 51, wherein the panels comprise panel sections, and the panel sections of one of the panels are attached together along hinged joints

53. (Withdrawn) The system of claim 51, wherein the panels are rigid.

54. (Withdrawn) The system of claim 51, wherein the panels are semi-rigid.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

55. (Withdrawn) The system of claim 1, wherein the landing pad further comprises a panel having first and second sides and energy-absorbing legs affixed to the first side of the panel, and the passive retaining medium is supported by the second side of the panel.

56. (Withdrawn) The system of claim 55, wherein the panel comprises panel sections attached together along hinged joints.

57. (Original) The system of claim 1, wherein the landing pad further includes:

load carrying members operative to transfer a load on the landing pad to a supporting surface; and

a securing system in load transferring communication with the load carrying members and configured to affix the landing pad to a supporting surface.

58. (Original) The system of claim 57, wherein the securing system comprises fittings disposed along edges of the landing pad.

59. (Original) The system of claim 58, wherein the fittings are removably attachable along edges of the landing pad.

60. (Original) The system of claim 58, wherein the fittings comprise clamp mechanisms attachable along edges of the landing pad.



Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

61. (Original) The system of claim 58, wherein the fittings are permanently affixed along edges of the landing pad.

62. (Original) The system of claim 57, wherein the securing system comprises fittings having rope or strap attachment components.

63. (Original) The system of claim 62, wherein the rope or strap attachment components comprise rings, loops, or eyes.

64. (Original) The system of claim 1, wherein the shoe is elongated from a front end to a back end and curved from the front end to the back end.

65. (Original) The system of claim 1, wherein the shoe further comprises a base, the passive retaining medium supported by the base.

66. (Withdrawn) The system of claim 65, wherein the base of the shoe comprises a flat pad.

67. (Original) The system of claim 65, wherein the base of the shoe is rigid.

68. (Original) The system of claim 65, wherein the base of the shoe is semi-rigid.

69. (Original) The system of claim 65, wherein the base of the shoe is flexible.

-10-

WEINGARTEN, SCHEURIN,  
GAGNEBIN & LESOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

70. (Original) The system of claim 1, further comprising a fastening system configured to fasten the shoe to the lowermost landing element of the aerial vehicle.

71. (Original) The system of claim 70, wherein the fastening system comprises at least one pair of upwardly extending tabs on opposed sides of the shoe and a fastening element fastenable between the tabs of a pair of tabs.

72. (Withdrawn) The system of claim 70, wherein the fastening system comprises a hose clamp.

73. (Original) The system of claim 1, further comprising a transport cart configured to store and transport the landing pad.

74. (Original) The system of claim 1, further comprising a transport cart configured to transport the aerial vehicle.

75. (Original) The system of claim 74, wherein the transport cart includes a hoist mechanism configured to hoist the aerial vehicle onto the transport cart.

76. (Original) The system of claim 74, wherein the transport cart includes a jack mechanism configured to jack the aerial vehicle onto the transport cart.

77. (Original) The system of claim 1, wherein the landing pad is securable to a ship's deck.

-11-

WEINGARTEN, SCHURIN,  
CAGNINI & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

78. (Original) The system of claim 1, wherein the landing pad is secured to a ship's deck.

79. (Original) The system of claim 1, wherein the landing pad is securable to a truck bed.

80. (Original) The system of claim 1, wherein the landing pad is secured to a truck bed.

81. (Original) The system of claim 1, wherein the landing pad is securable to an offshore platform.

82. (Original) The system of claim 1, wherein the landing pad is secured to an offshore platform.

83. (Original) The system of claim 1, wherein the landing pad is securable to ground.

84. (Original) The system of claim 1, wherein the landing pad is secured to ground.

85. (Withdrawn) A method for recovering an aerial vehicle using the recovery system of claim 1 comprising:

providing the landing pad on a support surface; and

landing the aerial vehicle with the shoe mounted on the lowermost landing element on the landing pad with the passive retaining medium of the landing pad and the passive retaining medium of the shoe in retention.

-12-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVITZ L.L.P.  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

86. (Withdrawn) The method of claim 85, further comprising:  
removing the shoe from the aerial vehicle while the vehicle  
is on the landing pad; and  
removing the aerial vehicle from the landing pad, leaving the  
shoe engaged on the landing pad.

87. (Withdrawn) A method for recovering an aerial vehicle  
comprising:  
providing a landing pad configured to be supported on a  
supporting surface, the landing pad comprising an upwardly facing  
capture surface comprising a passive retaining medium; and  
landing the aerial vehicle on the landing pad, a landing  
element of the aerial vehicle retained by the passive retaining  
medium on the capture surface.

88. (Withdrawn) An aerial vehicle recovery system comprising:  
an aerial vehicle having a landing element; and  
a passive retaining medium mounted to the landing element and  
configured to retain the aerial vehicle on a landing surface.

89. (Withdrawn) The system of claim 88, wherein the passive  
retaining medium comprises a passive engagement component.

90. (Withdrawn) The system of claim 88, wherein the passive  
retaining medium comprises a hook-to-hook fastener.

91. (Withdrawn) The system of claim 88, wherein the passive  
retaining medium comprises a hook and loop fastener.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

92. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises tape.

93. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises adhesive.

94. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises putty.

95. (Withdrawn) The system of claim 88, wherein the passive retaining medium is adhesively mounted to the landing element.

96. (Withdrawn) The system of claim 88, wherein the passive retaining medium is removably mounted to the landing element.

97. (Withdrawn) The system of claim 88, wherein the passive retaining medium is affixed to a shoe mounted to the landing element.

98. (Withdrawn) The system of claim 97, wherein the shoe is removably mounted to the landing element.

99. (Withdrawn) A method for recovering an aerial vehicle using the recovery system of claim 88, comprising:

landing the aerial vehicle with the passive retaining medium on the landing element of the aerial vehicle in retention with the landing surface.

Application No. 10/800,131  
Filed: March 12, 2004  
TC Art Unit: 3644  
Confirmation No.: 6931

100. (Withdrawn) The method of claim 99, wherein the landing surface comprises a ship's deck.
101. (Withdrawn) The method of claim 99, wherein the landing surface comprises a truck bed.
102. (Withdrawn) The method of claim 99, wherein the landing surface comprises an offshore platform.
103. (Withdrawn) The method of claim 99, wherein the landing surface comprises ground.
104. (Withdrawn) The method of claim 99, wherein the landing surface comprises a landing pad.
105. (Withdrawn) The method of claim 99, further comprising providing the landing surface with a passive retaining medium thereon.
106. (Withdrawn) The method of claim 105, wherein the landing surface has a hook and loop fastener thereon.
107. (Withdrawn) The method of claim 105, wherein the landing surface has a hook-to-hook fastener thereon.
108. (Withdrawn) The method of claim 105, wherein the landing surface has tape thereon.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

109. (Withdrawn) The method of claim 105, wherein the landing surface has adhesive thereon.

110. (Withdrawn) The method of claim 105, wherein the landing surface has putty thereon.